This listing will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

I.

(Currently amended): An acrylic elastomer composition vulcanizable by press Claim 1 vulcanization and oven vulcanization as secondary vulcanization under heating conditions, which comprises an aliphatic unsaturated dicarboxylic acid monoalkyl ester-copolymerized a carboxyl group-containing acrylic elastomer, (A) 0.1-5 parts by weight of a vulcanizing agent of polyvalent amine compound, and (B) 0.05-10 parts by weight of an antioxidant comprising a thiazole-based compound selected from 2-mercaptobenzothiazole, or its zinc salt, or dibenzothiazyl disulfide on the basis of 100 parts by weight of said acrylic elastomer, wherein the thiazole-based compound inhibits oxidative degradation of said acrylic elastomer composition.

Claims 2-4 (Canceled)

Claim 5 (Original): An acrylic elastomer composition according to Claim 1, wherein the thiazole-based compound is used together with an amine-based or phenol-based antioxidant.

Claims 6-7 (Canceled)

Claim 8 (Currently amended): An acrylic elastomer vulcanization-molded article, vulcanizationmolded mokied from an acrylic elastomer composition according to Claim 1.

Attorney Docket No. 14056-11

App. No. 10/594784 Reply to Final Office Action of October 6, 2009

Claim 9 (Canceled)

Claim 10 (Original): An acrylic elastomer vulcanization-molded article according to Claim 8.

which has parts in a wall thickness of not more than 30mm.

Claim 11 (Canceled)

Claim 12 (Original): An acrylic elastomer vulcanization-molded article according to Claim 10.

wherein the vulcanization-molded article having parts in a wall thickness of not more than 30mm

is a gasket or O ring.

Claim 13 (Canceled)

Claim 14 (Previously presented): A method of improving the compression set characteristics of

an acrylic elastomer composition which comprises a carboxyl group-containing acrylic

elastomer, which method comprises using a vulcanizing agent of a polyvalent amine compound

to prepare the acrylic elastomer composition and incorporating a thiazole-based compound

selected from 2-mercaptobenzothiazole, or its zinc salt, or dibenzothiazyl disulfide into the

acrylic elastomer composition and subjecting to press vulcanization and oven vulcanization as

secondary vulcanization by heating.

- 3 -

Reply to Final Office Action of October 6, 2009

Claim 15 (Previously presented): A method of improving the compression set characteristics of an acrylic elastomer composition according to claim 14, wherein the thiazole-based compound inhibits oxidative degradation of said acrylic elastomer composition.

Claim 16 (Previously presented) A method of improving the compression set characteristics of an acrylic elastomer composition according to claim 14 further comprising including an aminebased or phenol-based antioxidant into the acrylic elastomer composition, which functions as a primary antioxidant.